

# 5SNA 0500J650300

## HiPak IGBT Module

$V_{CE} = 6500 \text{ V}$   
 $I_C = 500 \text{ A}$

Ultra low-loss, rugged SPT+ chip-set  
 Smooth switching SPT+ chip-set for good EMC  
 High insulation package  
 AlSiC base-plate for high power cycling capability  
 AlN substrate for low thermal resistance  
 Improved high reliability package  
 Recognized under UL1557, File E196689



### Maximum rated values <sup>1)</sup>

| Parameter                      | Symbol       | Conditions  | min | max   | Unit               |
|--------------------------------|--------------|---|-----|-------|--------------------|
| Collector-emitter voltage      | $V_{CES}$    | $V_{GE} = 0 \text{ V}$ , $T_{vj} \geq 25 \text{ °C}$  |     | 6500  | V                  |
| DC collector current           | $I_C$        | $T_C = 85 \text{ °C}$ , $T_{vj} = 125 \text{ °C}$   |     | 500   | A                  |
| Peak collector current         | $I_{CM}$     | $t_p = 1 \text{ ms}$  |     | 1000  | A                  |
| Gate-emitter voltage           | $V_{GES}$    |   | -20 | 20    | V                  |
| Total power dissipation        | $P_{tot}$    | $T_C = 25 \text{ °C}$ , $T_{vj} = 125 \text{ °C}$   |     | 6250  | W                  |
| DC forward current             | $I_F$        |   |     | 500   | A                  |
| Peak forward current           | $I_{FRM}$    | $t_p = 1 \text{ ms}$  |     | 1000  | A                  |
| Surge current                  | $I_{FSM}$    | $V_R = 0 \text{ V}$ , $T_{vj} = 125 \text{ °C}$ ,<br>$t_p = 10 \text{ ms}$ , half-sinewave  |     | 5000  | A                  |
| IGBT short circuit SOA         | $t_{psc}$    | $V_{CC} = 4400 \text{ V}$ , $V_{CEM \text{ CHIP}} \leq 6500 \text{ V}$<br>$V_{GE} \leq 15 \text{ V}$ , $T_{vj} \leq 125 \text{ °C}$ |     | 10    | $\mu\text{s}$      |
| Isolation voltage              | $V_{isol}$   | 1 min, $f = 50 \text{ Hz}$  |     | 10200 | V                  |
| Junction temperature           | $T_{vj}$     |   |     | 125   | $^{\circ}\text{C}$ |
| Junction operating temperature | $T_{vj(op)}$ |   | -50 | 125   | $^{\circ}\text{C}$ |
| Case temperature               | $T_C$        |   | -50 | 125   | $^{\circ}\text{C}$ |
| Storage temperature            | $T_{stg}$    |   | -50 | 125   | $^{\circ}\text{C}$ |
| Mounting torques <sup>2)</sup> | $M_s$        | Base- heatsink, M6 screws   | 4   | 6     | Nm                 |
|                                | $M_{t1}$     | Main terminals, M8 screws   | 8   | 10    |                    |
|                                | $M_{t2}$     | Auxiliary terminals, M4 screws  | 2   | 3     |                    |

<sup>1)</sup> Maximum rated values indicate limits beyond which damage to the device may occur per IEC 60747

<sup>2)</sup> For detailed mounting instructions refer to ABB Document No. 5SYA 2039

### IGBT characteristic values <sup>3)</sup>

| Parameter  | Symbol               | Conditions   | min                       | typ  | max | Unit          |
|--|----------------------|--|---------------------------|------|-----|---------------|
| Collector (-emitter) breakdown voltage             | $V_{(BR)CES}$        | $V_{GE} = 0 \text{ V}$ , $I_C = 10 \text{ mA}$ , $T_{vj} = 25 \text{ °C}$  | 6500                      |      |     | V             |
| Collector-emitter <sup>4)</sup> saturation voltage | $V_{CE \text{ sat}}$ | $I_C = 500 \text{ A}$ , $V_{GE} = 15 \text{ V}$  | $T_{vj} = 25 \text{ °C}$  | 2.9  | 3.3 | V             |
|  |                      |  | $T_{vj} = 125 \text{ °C}$ | 3.9  | 4.5 | V             |
| Collector cut-off current                          | $I_{CES}$            | $V_{CE} = 6500 \text{ V}$ , $V_{GE} = 0 \text{ V}$   | $T_{vj} = 25 \text{ °C}$  |      | 8   | mA            |
|  |                      |  | $T_{vj} = 125 \text{ °C}$ | 40   | 70  | mA            |
| Gate leakage current                               | $I_{GES}$            | $V_{CE} = 0 \text{ V}$ , $V_{GE} = \pm 20 \text{ V}$ , $T_{vj} = 125 \text{ °C}$   | -500                      |      | 500 | nA            |
| Gate-emitter threshold voltage                     | $V_{GE(TO)}$         | $I_C = 160 \text{ mA}$ , $V_{CE} = V_{GE}$ , $T_{vj} = 25 \text{ °C}$  | 5.5                       |      | 7.5 | V             |
| Gate charge  | $Q_{ge}$             | $I_C = 500 \text{ A}$ , $V_{CE} = 3600 \text{ V}$ , $V_{GE} = -15 \text{ V} \dots 15 \text{ V}$  |                           | 5.3  |     | $\mu\text{C}$ |
| Input capacitance                                  | $C_{ies}$            | $V_{CE} = 25 \text{ V}$ , $V_{GE} = 0 \text{ V}$ , $f = 1 \text{ MHz}$ ,<br>$T_{vj} = 25 \text{ °C}$   |                           | 75.6 |     | nF            |
| Output capacitance                                 | $C_{oes}$            |  |                           | 4.4  |     | nF            |
| Reverse transfer capacitance                       | $C_{res}$            |  |                           | 1.3  |     | nF            |
| Internal gate resistance                           | $R_{Gint}$           |  |                           | 1.3  |     | $\Omega$      |
| Turn-on delay time                                 | $t_{d(on)}$          | $V_{CC} = 3600 \text{ V}$ , $I_C = 500 \text{ A}$ ,<br>$R_G = 3.9 \text{ }\Omega$ , $C_{GE} = 150 \text{ nF}$ ,<br>$V_{GE} = \pm 15 \text{ V}$ ,<br>$L_\sigma = 280 \text{ nH}$ , inductive load | $T_{vj} = 25 \text{ °C}$  | 780  |     | ns            |
|  |                      |  | $T_{vj} = 125 \text{ °C}$ | 710  |     | ns            |
| Rise time  | $t_r$                | $V_{CC} = 3600 \text{ V}$ , $I_C = 500 \text{ A}$ ,<br>$R_G = 3.9 \text{ }\Omega$ , $C_{GE} = 150 \text{ nF}$ ,<br>$V_{GE} = \pm 15 \text{ V}$ ,<br>$L_\sigma = 280 \text{ nH}$ , inductive load | $T_{vj} = 25 \text{ °C}$  | 200  |     | ns            |
|  |                      |  | $T_{vj} = 125 \text{ °C}$ | 240  |     | ns            |
| Turn-off delay time                                | $t_{d(off)}$         | $V_{CC} = 3600 \text{ V}$ , $I_C = 500 \text{ A}$ ,<br>$R_G = 22 \text{ }\Omega$ , $C_{GE} = 150 \text{ nF}$ ,<br>$V_{GE} = \pm 15 \text{ V}$ ,<br>$L_\sigma = 280 \text{ nH}$ , inductive load  | $T_{vj} = 25 \text{ °C}$  | 4750 |     | ns            |
|  |                      |  | $T_{vj} = 125 \text{ °C}$ | 5300 |     | ns            |
| Fall time  | $t_f$                | $V_{CC} = 3600 \text{ V}$ , $I_C = 500 \text{ A}$ ,<br>$R_G = 22 \text{ }\Omega$ , $C_{GE} = 150 \text{ nF}$ ,<br>$V_{GE} = \pm 15 \text{ V}$ ,<br>$L_\sigma = 280 \text{ nH}$ , inductive load  | $T_{vj} = 25 \text{ °C}$  | 530  |     | ns            |
|  |                      |  | $T_{vj} = 125 \text{ °C}$ | 660  |     | ns            |
| Turn-on switching energy                           | $E_{on}$             | $V_{CC} = 3600 \text{ V}$ , $I_C = 500 \text{ A}$ ,<br>$R_G = 3.9 \text{ }\Omega$ , $C_{GE} = 150 \text{ nF}$ ,<br>$V_{GE} = \pm 15 \text{ V}$ ,<br>$L_\sigma = 280 \text{ nH}$ , inductive load | $T_{vj} = 25 \text{ °C}$  | 2750 |     | mJ            |
|  |                      |  | $T_{vj} = 125 \text{ °C}$ | 3950 |     | mJ            |
| Turn-off switching energy                          | $E_{off}$            | $V_{CC} = 3600 \text{ V}$ , $I_C = 500 \text{ A}$ ,<br>$R_G = 22 \text{ }\Omega$ , $C_{GE} = 150 \text{ nF}$ ,<br>$V_{GE} = \pm 15 \text{ V}$ ,<br>$L_\sigma = 280 \text{ nH}$ , inductive load  | $T_{vj} = 25 \text{ °C}$  | 2700 |     | mJ            |
|  |                      |  | $T_{vj} = 125 \text{ °C}$ | 3500 |     | mJ            |
| Short circuit current                              | $I_{sc}$             | $t_{psc} \leq 10 \text{ }\mu\text{s}$ , $V_{GE} = 15 \text{ V}$ ,<br>$V_{CC} = 4400 \text{ V}$ ,<br>$V_{CEM \text{ CHIP}} \leq 6500 \text{ V}$   | $T_{vj} = 125 \text{ °C}$ | 2250 |     | A             |

<sup>3)</sup> Characteristic values according to IEC 60747 - 9

<sup>4)</sup> Collector-emitter saturation voltage is given at chip level

## Diode characteristic values <sup>5)</sup>

| Parameter                     | Symbol    | Conditions   | min                                   | typ  | max | Unit          |
|-------------------------------|-----------|--|---------------------------------------|------|-----|---------------|
| Forward voltage <sup>6)</sup> | $V_F$     | $I_F = 500 \text{ A}$  | $T_{vj} = 25 \text{ }^\circ\text{C}$  | 3.2  | 3.8 | V             |
|                               |           |  | $T_{vj} = 125 \text{ }^\circ\text{C}$ | 3.4  | 4.0 | V             |
| Reverse recovery current      | $I_{rr}$  |  | $T_{vj} = 25 \text{ }^\circ\text{C}$  | 610  |     | A             |
|                               |           |  | $T_{vj} = 125 \text{ }^\circ\text{C}$ | 650  |     | A             |
| Recovered charge              | $Q_{rr}$  | $V_{CC} = 3600 \text{ V}$ ,<br>$I_F = 500 \text{ A}$ ,<br>$V_{GE} = \pm 15 \text{ V}$ ,<br>$R_G = 3.9 \text{ } \Omega$ , $C_{GE} = 150 \text{ nF}$ ,<br>$dI/dt = 2 \text{ kA}/\mu\text{s}$<br>$L_\sigma = 280 \text{ nH}$ , inductive load | $T_{vj} = 25 \text{ }^\circ\text{C}$  | 550  |     | $\mu\text{C}$ |
|                               |           |  | $T_{vj} = 125 \text{ }^\circ\text{C}$ | 950  |     | $\mu\text{C}$ |
| Reverse recovery time         | $t_{rr}$  |  | $T_{vj} = 25 \text{ }^\circ\text{C}$  | 1800 |     | ns            |
|                               |           |  | $T_{vj} = 125 \text{ }^\circ\text{C}$ | 2800 |     | ns            |
| Reverse recovery energy       | $E_{rec}$ |  | $T_{vj} = 25 \text{ }^\circ\text{C}$  | 900  |     | mJ            |
|                               |           |  | $T_{vj} = 125 \text{ }^\circ\text{C}$ | 1850 |     | mJ            |

<sup>5)</sup> Characteristic values according to IEC 60747 - 2

<sup>6)</sup> Forward voltage is given at chip level

## Package properties <sup>7)</sup>

| Parameter   | Symbol             | Conditions  | min                                | typ   | max   | Unit             |
|---|--------------------|---|------------------------------------|-------|-------|------------------|
| IGBT thermal resistance junction to case                | $R_{th(j-c)IGBT}$  |   |                                    |       | 0.016 | K/W              |
| Diode thermal resistance junction to case               | $R_{th(j-c)DIODE}$ |   |                                    |       | 0.032 | K/W              |
| IGBT thermal resistance <sup>2)</sup> case to heatsink  | $R_{th(c-s)IGBT}$  | IGBT per switch, $\lambda$ grease = $1\text{W}/\text{m} \times \text{K}$  |                                    | 0.012 |       | K/W              |
| Diode thermal resistance <sup>2)</sup> case to heatsink | $R_{th(c-s)DIODE}$ | Diode per switch, $\lambda$ grease = $1\text{W}/\text{m} \times \text{K}$ |                                    | 0.024 |       | K/W              |
| Partial discharge extinction voltage                    | $V_e$              | $f = 50 \text{ Hz}$ , $Q_{PD} \leq 10 \text{ pC}$ (acc. To IEC 61287)     | 5100                               |       |       | V                |
| Comparative tracking index                              | CTI                |   |                                    | > 600 |       |                  |
| Module stray inductance                                 | $L_{\sigma CE}$    |   |                                    | 27    |       | nH               |
| Resistance, terminal-chip                               | $R_{CC'+EE'}$      |   | $T_C = 25 \text{ }^\circ\text{C}$  | 0.1   |       | $\text{m}\Omega$ |
|   |                    |   | $T_C = 125 \text{ }^\circ\text{C}$ | 0.15  |       |                  |


<sup>2)</sup> For detailed mounting instructions refer to ABB Document No. 5SYA 2039

## Mechanical properties <sup>7)</sup>


| Parameter                 | Symbol    | Conditions                              | min            | typ            | max | Unit |
|---------------------------|-----------|---|----------------|----------------|-----|------|
| Dimensions                | L x W x H | Typical                                 |                | 130 x 140 x 48 |     | mm   |
| Clearance distance in air | $d_a$     | according to IEC 60664-1 and EN 50124-1 | Term. to base: | 40             |     | mm   |
|                           |           |   | Term. to term: | 26             |     |      |
| Surface creepage distance | $d_s$     | according to IEC 60664-1 and EN 50124-1 | Term. to base: | 64             |     | mm   |
|                           |           |   | Term. to term: | 56             |     |      |
| Mass                      | m         |   |                | 1010           |     | g    |

<sup>7)</sup> Package and mechanical properties according to IEC 60747 - 15

## Electrical configuration



## Outline drawing <sup>2)</sup>



Note: all dimensions are shown in millimeters

<sup>2)</sup> For detailed mounting instructions refer to ABB Document No. 5SYA 2039

This is an electrostatic sensitive device, please observe the international standard IEC 60747-1, chap. IX. This product has been designed and qualified for Industrial Level.




Fig. 1 Typical on-state characteristics, chip level




Fig. 2 Typical transfer characteristics, chip level




Fig. 3 Typical output characteristics, chip level




Fig. 4 Typical output characteristics, chip level




Fig. 5 Typical switching energies per pulse vs. collector current




Fig. 6 Typical switching energies per pulse vs. gate resistor




Fig. 7 Typical switching times vs. collector current




Fig. 8 Typical switching times vs. gate resistor




Fig. 9 Typical capacitances vs. collector-emitter voltage




Fig. 10 Typical gate charge characteristics




Fig. 11 Turn-off safe operating area (RBSOA)




Fig. 12 Typical reverse recovery characteristics vs. forward current




Fig. 13 Typical reverse recovery characteristics vs. di/dt




Fig. 14 Typical diode forward characteristics chip level




Fig. 15 Safe operating area diode (SOA)






Fig. 16 Thermal impedance vs. time

Analytical function for transient thermal impedance:

$$Z_{th(j-c)}(t) = \sum_{i=1}^n R_i (1 - e^{-t/\tau_i})$$

|       |                       |       |      |   |   |   |
|-------|-----------------------|-------|------|---|---|---|
|       | i                     | 1     | 2    | 3 | 4 | 5 |
| IGBT  | R <sub>i</sub> (K/kW) | 12.75 | 2.99 |   |   |   |
|       | τ <sub>i</sub> (ms)   | 151   | 5.84 |   |   |   |
| DIODE | R <sub>i</sub> (K/kW) | 25.5  | 6.3  |   |   |   |
|       | τ <sub>i</sub> (ms)   | 144   | 5.83 |   |   |   |

**Related documents:**

- 5SYA 2042 Failure rates of HiPak modules due to cosmic rays
- 5SYA 2043 Load - cycle capability of HiPaks
- 5SYA 2045 Thermal runaway during blocking
- 5SYA 2053 Applying IGBT
- 5SYA 2058 Surge currents for IGBT diodes
- 5SZK 9111 Specification of environmental class for HiPak Storage
- 5SZK 9112 Specification of environmental class for HiPak Transportation
- 5SZK 9113 Specification of environmental class for HiPak Operation (Industry)
- 5SZK 9120 Specification of environmental class for HiPak

ABB Switzerland Ltd.  
Semiconductors  
Fabrikstrasse 3  
CH-5600 Lenzburg  
Switzerland

Phone: +41 58 586 1419  
Fax: +41 58 586 1306  
E-Mail: abbsem@ch.abb.com  
Internet: www.abb.com/semiconductors

We reserve the right to make technical changes or to modify the contents of this document without prior notice.

We reserve all rights in this document and the information contained therein. Any reproduction or utilization of this document or parts thereof for commercial purposes without our prior written consent is forbidden.

Any liability for use of our products contrary to the instructions in this document is excluded.